

Cylinders with integrated guide Series QC

1

Double-acting, magnetic piston, guided
 ø 20, 25, 32, 40, 50, 63



- » Magnetic sensors can be mounted on both sides
- » Two versions: Ball bearing guide and bronze bushings
- » Movement and guidance in one unit

Both models are equipped with fixed cushioning to prevent direct impact with the end covers. The design of the cylinder body allows the mounting of the cylinder using either top, bottom or side faces. Several "T" shaped grooves in two faces allow sensors to be fitted in a number of positions.

The Series QC compact cylinders have been designed to be used in applications where space is limited. These cylinders are available in two versions, one with sintered bronze bushes (model QCT) and the other with linear ball bearings (model QCB). The QCT version would normally be selected when the side loads applied to the cylinder are high. Model QCB cylinders are suitable for high precision and fast cycling applications.

GENERAL DATA

Type of construction	compact guided QCT = sintered bronze bushes QCB = linear ball bearings
Operation	double-acting
Materials	- anodized AL body - flange zinc-plated steel - rolled stainless steel piston rod AISI 303 - PU seals rolled stainless steel 420B columns (QCT) hardened steel C50 columns (QCB) PU seals
Mounting	threaded and non-threaded holes in the body
Strokes min. max	see table
Operating temperature	0°C ÷ 80°C (with dry air - 20°C)
Speed	50 ÷ 500 mm/s
Operating pressure	1 ÷ 10 Bar
Fluid	clean air, non lubricated If lubricated air is used, it is recommended to use oil ISOVG32. Once applied the lubrication should never be interrupted.

TABLE SHOWING THE STANDARD STROKES FOR DOUBLE - ACTING CYLINDERS SERIES QC

■ = Double-acting

∅	20	25	30	40	50	75	100	125	150	175	200
20	■		■	■	■	■	■	■	■	■	■
25	■		■	■	■	■	■	■	■	■	■
32		■			■	■	■	■	■	■	■
40		■			■	■	■	■	■	■	■
50		■			■	■	■	■	■	■	■
63		■			■	■	■	■	■	■	■

CODING EXAMPLE


QC	T	2	A	020	A	050
-----------	----------	----------	----------	------------	----------	------------

QC	SERIES
T	VERSION T = sintered bronze bushes B = linear ball bearings
2	OPERATIONS 2 = double-acting
A	MATERIALS A = anodized aluminium body rolled stainless steel 303 piston rod rolled stainless steel 420B columns for QCT hardened steel C50 columns for QCB
020	BORE 20 mm 25 mm 32 mm 40 mm 50 mm 63 mm
A	TYPE OF DESIGN A = standard
050	STROKE (see table)

TABLE OF PERMISSIBLE LOADS (F)

FOR SINTERED BRONZE BUSHES
(QCT) - FOR LINEAR BALL
BEARINGS (QCB)

F (N) 1N = 0.102 kgf
Ex.: QCT2A025A020 = F = 140N




STROKE												
Ø	Mod	20	25	30	40	50	75	100	125	150	175	200
20	QCT	100	-	93	81	73	114	93	98	85	75	67
25	QCT	140	-	120	115	103	165	135	150	131	116	104
32	QCT	-	253	-	-	214	225	208	225	198	176	159
40	QCT	-	251	-	-	197	215	206	224	196	175	157
50	QCT	-	317	-	-	273	267	299	257	225	200	179
63	QCT	-	316	-	-	273	267	299	257	225	200	179
20	QCB	110	-	100	125	121	90	86	69	58	49	43
25	QCB	142	-	85	154	148	106	82	97	81	70	61
32	QCB	-	222	-	-	91	167	129	145	122	104	90
40	QCB	-	221	-	-	93	167	128	145	121	104	90
50	QCB	-	203	-	-	152	161	193	156	130	110	95
63	QCB	-	201	-	-	151	158	195	157	130	110	94

TABLE OF PERMISSIBLE MOMENTS (M)







FOR SINTERED BRONZE BUSHES
(QCT) - FOR LINEAR BALL
BEARINGS (QCB)

M (N*m) 1N*m = 0,102 kgf *m
Ex.: QCT2A025A020 = M = 3,4 Nm



STROKE												
Ø	Mod	20	25	30	40	50	75	100	125	150	175	200
20	QCT	1,7	-	1,5	1,2	1,0	2,9	2,8	2,6	2,3	2,0	1,8
25	QCT	3,4	-	2,9	3,6	3,3	4,2	4,3	3,8	3,2	2,7	2,3
32	QCT	-	6,7	-	-	6,5	7,2	7,0	6,6	5,6	4,8	4,1
40	QCT	-	8,7	-	-	7,3	9,2	8,8	9,6	8,4	7,5	6,7
50	QCT	-	15,4	-	-	12,9	12,6	13,4	12,1	11,3	10,7	8,8
63	QCT	-	15,1	-	-	14,3	16,6	17	14	11,3	9,7	9,1
20	QCB	3,0	-	2,7	3,4	3,3	2,4	2,3	1,9	1,6	1,3	1,2
25	QCB	3,5	-	2,7	4,9	4,7	3,4	2,6	3,1	2,6	2,2	2,0
32	QCB	-	6,3	-	-	3,6	6,5	5,1	5,7	4,8	4,1	3,5
40	QCB	-	8,5	-	-	4,0	7,2	5,5	6,2	5,2	4,5	3,9
50	QCB	-	11,1	-	-	8,3	8,8	10,6	8,6	7,1	6,0	5,2
63	QCB	-	8,3	-	-	7,2	9,8	12,1	9,7	8,1	6,8	5,8

Cylinder Series QC



+ = add the stroke

DIMENSIONS

Dimension Ø2 (mm)	Ø 20	Ø 25	Ø 32	Ø 40	Ø 50	Ø 63	Dimension Ø4 (mm)	Ø 20	Ø 25	Ø 32	Ø 40	Ø 50	Ø 63
20 + 30	24	24	24	24	24	28	20 + 30	29	29	33	34	36	38
40 + 100	44	44	48	48	48	52	40 + 100	39	39	45	46	48	50
125 + 200	120	120	124	124	124	128	125 + 200	77	77	83	84	86	88

DIMENSIONS

Ø	A	gC	nD	E1	E2	F	F1	F2	F3	F4	F5	F6	G1	G2	H	H1	L1	L2	M1	M2	N	Ø1	Ø3	P1/P2	P3	Q	R	S	Y	Y1	Y2	Y3	Y4	X	X1	X2	J	K
20	10	12	10	70	18	G1/8	10,5	10,5	25	12,5	11,5	10,5	81	30	72	54	37	53	83	36	24	17	28	M5X08	M6X1	13	12	6	28	3	3,5	3	6	5,5	9,5	5,5	44	M5
25	10	16	12	78	26	G1/8	11,5	8	28,5	12,5	13,5	11,5	91	40	82	64	37,5	53,5	93	42	30	17	34	M6X1	M6X1	15	12	6	34	4	4,5	3	6	5,5	9,5	5,5	50	M5
32	12	20	16	96	30	G1/8	12,5	9,5	34	7	15	12,5	110	45	98	78	37,5	59,5	112	48	34	21	42	M8X1,25	M8X1,25	20	16	10	42	4	4,5	3	6	6,5	11	7,5	63	M6
40	12	20	16	104	30	G1/8	13	12	38	13	18	13	118	45	106	86	44	66	120	54	40	22	50	M8X1,25	M8X1,25	20	16	10	50	4	4,5	3	6	6,5	11	7,5	72	M6
50	15	25	20	130	40	G1/4	14	11	47	8	215	12	146	60	130	110	44	72	148	64	46	24	66	M10X1,25	M10X1,25	22	20	13	66	5	6	4	8	8,5	14	9	92	M8
63	15	25	20	130	40	G1/4	14,5	11,4	55	12	28	14,5	158	70	142	124	49	77	162	78	58	24	80	M10X1,25	M10X1,25	22	20	13	80	5	6	4	8	8,5	14	9	110	M10

Fixed dimensions for Mod. QCB

Dimensions L3 and B for different strokes of Mod. QCB

See drawing page
1.4.05.04

DIMENSIONS																
Ø	Dimension L3	20-30	25-50	25-75	40-100	75-100	100-200	125-200	Dimension B	20-30	25-50	25-75	40-100	75-100	100-200	125-200
20		72	-	-	75	-	-	85		19	-	-	22	-	-	32
25		74,5	-	-	85,5	-	-	98		21	-	-	32	-	-	44,5
32		-	86	-	-	95	-	110		-	26,5	-	-	35,5	-	50,5
40		-	86	-	-	95	-	110		-	20	-	-	29	-	44
50		-	-	93	-	-	112	-		-	-	21	-	-	40	-
63		-	-	93	-	-	112	-		-	-	16	-	-	35	-

Fixed dimensions for Mod. QCT

Dimensions L3 and B for different strokes of Mod. QCT

See drawing page
1.4.05.04

DIMENSIONS																
Ø	Dimension L3	20-50	20	25	30-50	25-200	75-200	50-200	Dimension B	20-50	20	25	30-50	25-200	75-200	50-200
20		74,5	-	-	-	-	79,5	-		21,5	-	-	-	-	26,5	-
25		-	74,5	-	80,5	-	85	-		-	21	-	27	-	31,5	-
32		-	-	73,5	-	-	-	91,5		-	-	14	-	-	-	32
40		-	-	73,5	-	-	-	91,5		-	-	7,5	-	-	-	25,5
50		-	-	-	-	98,5	-	-		-	-	-	-	26,5	-	-
63		-	-	-	-	98,5	-	-		-	-	-	-	21,5	-	-